

IntegralFanAirFlowMeter



Handheldanemometer8903/8904/8906



- ▲ FASHIONDESIGNWITHONEHEADOPERATION
- ▲ INTEGRALFANWITHTEMP.SENSORBUILT-IN
- ▲ MEASURES AIRVELOCITY,TEMPERATURE
- ▲ WINDSPEEDMETRICANDIMPERIALUNITSSELECTABLE
- ▲ TEMP.UNITS °C/°FSELECTABLE
- ▲ DISPLAY MAX./MIN./AVG.VALUE
- ▲ HOLDFUNCTIONTOFREEZECURRENTREADINGS
- ▲ AUTOPOWEROFFIN20MINSINACTIVITYTOSAVEPOWER
- ▲ SLEEPANDNON-SLEEPMODESELECTABLE
- ▲ LCDDISPLAYFLASHAS LOWBATTERYINDICATOR
- ▲ 8904FEATURES:8P OINTSVELOCITYAVERAGE
- ▲ 8906FEATURES:8P OINTSVELOCITYAVERAGE,VOLUME

	8903	8904	8906
Windspeedrange	0.4~30m/s;80~5900ftm		
Windspeedaccuracy	+/-3%offullscale		
Airtemp.range	-10~50.0C		
Airtemp.resolution	0.1C/F°		
Airtemp.accuracy	+/-1C		
Windspeedunit(m/s)	YES	YES	YES
Windspeedunit(ft/m)	YES	YES	YES
Windspeedunit(KM/H)	N/A	YES	YES
Windspeedunit(MPH)	N/A	YES	YES
Windspeedunit(knot)	N/A	YES	YES
Airvolumeunit(cms)	N/A	N/A	YES
Airvolumeunit(cfm)	N/A	N/A	YES
Temp.responsetime	60seconds(typical)		
LCDupdate	everysecond		
Airvolumedisplay	0to9999m ³ /s		
Airvolumeresolution	0.1(0to999.9)or1(1000to9999)		
LCDsize	34(H)x40(W)mm		
Operatingtemp.	0~50C		
OperatingRH%	Humidity<80%		
Storage temp.	-10~50C		
StorageRH%	Humidity<9 0%		
PCLink	YES		
8pointsvelocityaverage	N/A	YES	YES
Battery life	100hours		
Dimension(mm)	183x76x45(meter);70(impeller)		
Weight	~150g		
Battery	9Vbatteryx1 pc		
Optionalaccessory	Softwarekit		
StandardPackage	Meter/Battery/Manual/Hardcarrycase		

Optional



RS232cable&s_oftware
P/N:VZRS232BN
USBcable&s_oftware
P/N:VZUSBAZM