

Fone: 11 5096-4654 - www.vectus.com.br

Gasmaster Handheld Gas Monitors

CO, CO2, Ammonia, Formaldehyde, Ozone, VOC and over 20 other gases

Handheld gas monitors are suitable for indoor, industrial and outdoor air quality monitoring. Compatible with over 30 different interchangeable sensor heads, one monitor can be used to measure multiple gases and concentrations. Interchangeable sensor heads also make servicing the monitors as simple as replacing the old head with a new one.

Applications

- IAQ Investigations
- Environmental Monitoring
- Industrial Processing
- Food and Pharmaceutical
- Green Building/LEED Certification



Features & Benefits

- Simultaneous measurements of gas concentration, temperature, and humidity
- Model 2710 is a simple, easy-to-use, low-cost monitor
- Model 2750 has data logging function and USB interface for PC communication
- Multi-gas sensor heads are available for IAQ survey applications
- Over 8 hours battery life (recharge in 2 hrs)
- Span and zero calibration
- The gas monitor is fully compatible with all gas sensors

- Sensor heads for handheld units are interchangeable without recalibration of main unit
- More than 20 gases including: Ammonia, Carbon monoxide, Carbon Dioxide, Hydrogen, Formaldehyde, Hydrogen sulphide, Methane, Ozone, Nitrogen Dioxide, Perchloroethylene, Sulphur dioxide and VOCs



Handheld Gas Monitor Specifications						
	200					
Model	2710	2750				
Measurement Units	ppm or mg/m ³	ppm or mg/m ³				
T/H Sensor	available as option	available as option				
On-board alarm	I	0				
Remote Sensor	0	0				
Datalogging		8,188 measurements				
Interface	-	USB				
Analog Output	_	0 to 5 V				
Power supply	Li-ion battery pack or AC adapter	Li-ion battery pack or AC adapter				
Dimensions	W7.4" x H4.8" x D2.1"	W7.4" x H4.8" x D2.1"				
Weight	1.0 lbs (460 g)	1.0 lbs (460 g)				

Specifications subject to change.

Gas Sensor Head Specifications							
Gas Sensor Heads	Range (ppm)	Accuracy	Resolution				
Ammonia	0 - 100	<+/-5 ppm + 15%	0.1 ppm				
Ammonia	0 - 1000	<+/-0.5 ppm + 10%	1 ppm				
Carbon monoxide	0 - 100	<+/-1 ppm (0 to 10 ppm) <+/-10% (10 to 100 ppm)	0.1 ppm				
Carbon monoxide	0 - 1000	<+/-2 ppm + 15%	1 ppm				
Carbon dioxide	0 - 2000	<+/-10 ppm + 5%	1 ppm				
Carbon dioxide	0 - 5000	<+/-20 ppm + 5%	1 ppm				
Formaldehyde	0 - 10	<+/-0.05 ppm (0 to 0.5 ppm) <+/-10% (0.5 to 10 ppm)	0.01 ppm				
Hydrogen sulphide	0 - 10	<+/-0.5 ppm (0 to 5 ppm) <+/-10% (0.5 to 10 ppm)	0.01 ppm				
Ozone	0 - 0.05	<+/-0.002 ppm	0.001 ppm				
Ozone	0 - 10	<+/-0.01 ppm + 7.5%	0.01 ppm				
Nitrogen dioxide	0 - 1	<+/-0.02 ppm (0 to 0.2 ppm) <+/-10% (0.2 to 1 ppm)	0.001 ppm				
NMHC	0 - 25	<+/-0.1 ppm + 10 %	0.1 ppm				
Sulfur dioxide	0 - 10	<+/-0.05 ppm (0 to 0.5 ppm) <+/-10% (0.5 to 10 ppm)	0.01 ppm				
VOC	0 - 25	<+/-0.1 ppm + 10 % 0.1 ppm					
VOC	0 - 500	<+/-5 ppm + 10 % 1 ppm					

* Other specific concentrations available on request

Multi-Gas Sensor Heads	Sensor	Range (ppm)	Accuracy	Resolution
MS1	CO2	0-2000	<+/-10 ppm + 5%	1 ppm
	CO	0-100	<+/-1ppm	0.1 ppm
MS2	CO2	0-2000	<+/-10 ppm + 5%	1 ppm
	CO	0-100	<+/-1ppm	0.1 ppm
	VOC (PID)	0-20	<+/-0.02 ppm + 10%	0.01 ppm

Compatible for Indoor Air Quality Survey

- Carbon Monoxide (CO)
- Carbon Dioxide (CO₂)
- Multi-gas sensor (MS1 and MS2)
- Ozone (O₃)
- Sulfur Dioxide (SO₂)
- Formaldohyde (CH2O)
- Volatile Organic Compounds (VOC)

Compatible for Environmental Survey

- Nitrogen Dioxide (NO2)
- Hydrogen Sulphide (H2S)
- Sulfur Dioxide (SO₂)
- Carbon Monoxide (CO)
- Carbon Dioxide (CO₂)
- Volatile Organic Compounds (VOC)
- Ozone (O3)
- Ammonia (NH₃)
- Non-Methane Hydrocarbon (NMHC)

Distributed by:

Vectus Importatum

Av. da Invernada, 12 Vila Congonhas São Paulo - SP

Tel: +55 11 5096-4654

E-mail: vectus@vectus.com.br

Copyright © 2012 by KANOMAX USA, Inc.