

# Handheld IAQ Monitor

## Model 2211

### Multi-Function Indoor Air Quality Monitor

The Kanomax IAQ Monitor 2211 features quick start-up and high accuracy in measuring carbon dioxide and carbon monoxide concentration levels in the environment. Temperature and humidity are also simultaneously measured in a handy lightweight design.

### Applications

- IAQ Investigation
- Ventilation Testing
- Thermal Comfort Control
- Monitoring Toxic Gas

### Features

- Simultaneous measurements of CO, CO<sub>2</sub>, Temperature, and Relative humidity
- Calculates Dew point, Wet bulb temperature, Absolute humidity, Humidity Ratio, and % Outside Air
- Data HOLD, Record and recall MAX / MIN / AVG
- Store up to 1500 measurements
- Easy user self calibration
- PC interface with RS232C/USB and software for real-time
- Complete with probe with 79 in (2m) cable, probe stand, calibration cap & connection tube, data processing software, RS232C cable, Serial - USB converter, 6 pc. AA batteries, carrying case, and NIST-Traceable calibration certificate



### Handheld IAQ Monitor Model 2211 Specifications

<b>Carbon Monoxide (CO)</b>	0 to 500 ppm
<b>Accuracy</b>	+/- 3% of reading
<b>Carbon Dioxide (CO<sub>2</sub>)</b>	0 to 5000 ppm
<b>Accuracy</b>	+/- 3% of reading
<b>Temperature Ranges</b>	-4 to 140 °F (-20 to 60 °C)
<b>Accuracy</b>	+/- 1.0 °F (0.5 °C)
<b>Relative Humidity Ranges</b>	2.0 to 98.0 %RH
<b>Accuracy</b>	+/- 2% of reading
<b>Interface</b>	RS232C or USB
<b>Datalogging</b>	1500 measurements
<b>Analog Output</b>	0 to 1 V *Option
<b>Power Supply</b>	6 x AA Batteries or AC Adapter
<b>Dimensions</b>	W3.4" x H7.4" x D1.6"
<b>Weight</b>	0.9 lbs (400 g)

Specifications are subject to change without notice.

Distributed by:

## Vectus Importatum

Av. da Invernada, 12

Vila Congonhas

São Paulo - SP

Tel: +55 11 5096-4654

E-mail: [vectus@vectus.com.br](mailto:vectus@vectus.com.br)